

## Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: 159681-  
Product name: HYDRO MICACEO MT

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: One component water based topcoat with micaceous iron oxide.

#### 1.3. Details of the supplier of the safety data sheet

Name: Ti.Pi.Ci. S.a.s.  
Full address: Via Val Lerone, 21  
District and Country: 16011 Arenzano (GE)  
Italy  
Tel. +39 010 9111368  
Fax +39 010 9134188

e-mail address of the competent person  
responsible for the Safety Data Sheet

laboris@tipici.net

#### 1.4. Emergency telephone number

For urgent inquiries refer to

Centro Antiveleni di Bergamo +39800883300 (Azienda Ospedaliera Papa Giovanni XXII - Bergamo)  
Centro Antiveleni di Firenze +39055/7947819 (CAV Ospedale Careggi - Firenze)  
Centro Antiveleni di Foggia +39800183459 (Az. Osp. Univ. Foggia - Foggia)  
Centro Antiveleni di Milano +3902/66101029 (CAO Ospedale Niguarda Cà Granda - Milano)  
Centro Antiveleni di Napoli +39081/5453333 (CAV Ospedale Cardarelli - Napoli)  
Centro Antiveleni di Pavia +390382/24444 (CAV IRCCS Fondazione Maugeri - Pavia)  
Centro Antiveleni di Roma +3906/3054343 (CAV Policlinico Gemelli - Roma)  
Centro Antiveleni di Roma +3906/49978000 (CAV Policlinico Umberto I - Roma)  
Centro Antiveleni di Roma +3906/68593726 (CAV Osp. Pediatrico Bambino Gesù - Roma)  
Centro Antiveleni di Verona +39800011858 (Azienda Ospedaliera Integrata - Verona)

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Hazardous to the aquatic environment, chronic toxicity, category 3 H412 Harmful to aquatic life with long lasting effects.

**2.2. Label elements**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:

**H412** Harmful to aquatic life with long lasting effects.  
**EUH208** Contains: COBALT BIS 2-ETHYL HEXANOATE  
 May produce an allergic reaction.

Precautionary statements:

**P273** Avoid release to the environment.

VOC (Directive 2004/42/EC):

One - pack performance coatings.

VOC given in g/litre of product in a ready-to-use condition :	15,62
Limit value:	140,00

**2.3. Other hazards**

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

**SECTION 3. Composition/information on ingredients****3.2. Mixtures**

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
<b>Aluminum hydrogen triphosphate</b>		
INDEX -	$1,5 \leq x < 2$	Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335
EC 237-714-9		
CAS 13939-25-8		
<b>ZINC OXIDE</b>		
INDEX 030-013-00-7	$1 \leq x < 1,5$	Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1
EC 215-222-5		
CAS 1314-13-2		
REACH Reg. 01-2119463881-32		
<b>CALCIUM BIS 2-ETHYLHEXANOATE</b>		

**159681- - HYDRO MICACEO MT**

INDEX -	0,2 ≤ x < 0,3	Repr. 2 H361d, Eye Dam. 1 H318
EC 205-249-0		
CAS 136-51-6		
REACH Reg. 01-2119978297-19-0000		
<b>COBALT BIS 2-ETHYL HEXANOATE</b>		
INDEX -	0,1 ≤ x < 0,2	Repr. 2 H361f, Eye Irrit. 2 H319, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 3 H412
EC 205-250-6		
CAS 136-52-7		
<b>TRIETHYLAMINE</b>		
INDEX 612-004-00-5	0,1 ≤ x < 0,2	Flam. Liq. 2 H225, Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Corr. 1A H314, Eye Dam. 1 H318, STOT SE 3 H335 STOT SE 3 H335: ≥ 1%
EC 204-469-4		
CAS 121-44-8		LD50 Oral: 460 mg/kg, STA Dermal: 1100 mg/kg, LC50 Inhalation vapours: 14,5 mg/l/4h
<b>QUARTZ</b>		
INDEX -	0 ≤ x < 0,1	STOT RE 2 H373
EC 238-878-4		
CAS 14808-60-7		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## SECTION 4. First aid measures

### 4.1. Description of first aid measures

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

**SKIN:** Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

**INHALATION:** Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

**INGESTION:** Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

## SECTION 5. Firefighting measures

### 5.1. Extinguishing media

#### SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

#### UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

## 5.2. Special hazards arising from the substance or mixture

### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

## 5.3. Advice for firefighters

### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage

### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s)

Information not available

**SECTION 8. Exposure controls/personal protection****8.1. Control parameters**

## Regulatory References:

DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2021

**ZINC OXIDE****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	DEU	2		4		INHAL
MAK	DEU	0,1		0,4		RESP
VLA	ESP	2		10		
VLEP	FRA	5				
TLV-ACGIH		2		10		RESP

**COBALT BIS 2-ETHYL HEXANOATE****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
WEL	GBR	0,1				As Co
TLV-ACGIH		0,02				INHAL Co

**TRIETHYLAMINE****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	4,2	1	8,4 (C)	2 (C)	SKIN
MAK	DEU	4,2	1	8,4	2	
VLA	ESP	8,4	2	12,6	3	SKIN
VLEP	FRA	4,2	1	12,6	3	SKIN
VLEP	ITA	8,4	2	12,6	3	SKIN
WEL	GBR	8	2	17	4	SKIN
OEL	EU	8,4	2	12,6	3	SKIN
TLV-ACGIH			0,5		1	SKIN

**QUARTZ****Threshold Limit Value**

**159681- - HYDRO MICACEO MT**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
VLA	ESP		0,05			RESP
VLEP	FRA	0,1				RESP
VLEP	ITA	0,1				RESP
OEL	EU	0,1				RESP
TLV-ACGIH		0,025				RESP

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

## 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

## SECTION 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
------------	-------	-------------

Appearance	liquid
Colour	different colours
Odour	slightly aromatic
Melting point / freezing point	not available
Initial boiling point	not available
Flammability	not available
Lower explosive limit	not available
Upper explosive limit	not available
Flash point	> 65 °C
Auto-ignition temperature	not available
Decomposition temperature	not available
pH	8
Kinematic viscosity	not available
Solubility	miscible with water
Partition coefficient: n-octanol/water	not available
Vapour pressure	not available
Density and/or relative density	1,52 (+-0,05) Kg/l
Relative vapour density	not available
Particle characteristics	not applicable

## 9.2. Other information

### 9.2.1. Information with regard to physical hazard classes

Information not available

### 9.2.2. Other safety characteristics

VOC (Directive 2004/42/EC) : 1,03 % - 15,62 g/litre

VOC (volatile carbon) 0,48 % - 7,32 g/litre

## SECTION 10. Stability and reactivity

### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

**10.5. Incompatible materials**

Information not available

**10.6. Hazardous decomposition products**

Information not available

**SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

Not classified (no significant component)

ATE (Oral) of the mixture:

Not classified (no significant component)

ATE (Dermal) of the mixture:

Not classified (no significant component)

CALCIUM BIS 2-ETHYLHEXANOATE

**159681- - HYDRO MICACEO MT**

LD50 (Dermal): > 2000 mg/kg Rat - Wistar  
LD50 (Oral): 2043 mg/kg Rat - Fischer 344

**COBALT BIS 2-ETHYL HEXANOATE**

LD50 (Dermal): > 2000 mg/kg Rat - Wistar  
LD50 (Oral): 3129 mg/kg Rat - Sprague-Dawley

**TRIETHYLAMINE**

LD50 (Dermal): 580 mg/kg Rabbit  
STA (Dermal): 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP  
(figure used for calculation of the acute toxicity estimate of the mixture)

LD50 (Oral): 460 mg/kg Rat  
LC50 (Inhalation vapours): 14,5 mg/l/4h Rat

**SKIN CORROSION / IRRITATION**

Does not meet the classification criteria for this hazard class

**SERIOUS EYE DAMAGE / IRRITATION**

Does not meet the classification criteria for this hazard class

**RESPIRATORY OR SKIN SENSITISATION**

May produce an allergic reaction.

Contains:

COBALT BIS 2-ETHYL HEXANOATE

**GERM CELL MUTAGENICITY**

Does not meet the classification criteria for this hazard class

**CARCINOGENICITY**

Does not meet the classification criteria for this hazard class

**REPRODUCTIVE TOXICITY**

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

**11.2. Information on other hazards**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

**SECTION 12. Ecological information**

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

**12.1. Toxicity**

## CALCIUM BIS 2-ETHYLHEXANOATE

LC50 - for Fish	> 100 mg/l/96h <i>Oryzias latipes</i>
EC50 - for Crustacea	910 mg/l/48h <i>Daphnia magna</i>
EC50 - for Algae / Aquatic Plants	49,3 mg/l/72h <i>Desmodesmus subspicatus</i>

## COBALT BIS 2-ETHYL HEXANOATE

LC50 - for Fish	275 mg/l/96h <i>Fundulus heteroclitus</i>
-----------------	---

## ZINC OXIDE

LC50 - for Fish	1,1 mg/l/96h <i>Oncorhynchus mykiss</i>
EC50 - for Crustacea	1,7 mg/l/48h <i>Daphnia magna</i>
EC50 - for Algae / Aquatic Plants	0,14 mg/l/72h <i>Pseudokirchnerella subcapitata</i>
Chronic NOEC for Fish	0,53 mg/l
Chronic NOEC for Algae / Aquatic Plants	0,024 mg/l

**12.2. Persistence and degradability**

## CALCIUM BIS 2-ETHYLHEXANOATE

Solubility in water	> 10000 mg/l
---------------------	--------------

Rapidly degradable

## COBALT BIS 2-ETHYL HEXANOATE

Solubility in water	> 10000 mg/l
---------------------	--------------

Rapidly degradable  
TRIETHYLAMINE

Solubility in water > 10000 mg/l

Rapidly degradable  
ZINC OXIDE

Solubility in water 2,9 mg/l

NOT rapidly degradable

### 12.3. Bioaccumulative potential

CALCIUM BIS 2-ETHYLHEXANOATE

Partition coefficient: n-octanol/water 2,96

TRIETHYLAMINE

Partition coefficient: n-octanol/water 1,45

BCF < 0,5

ZINC OXIDE

BCF > 175

### 12.4. Mobility in soil

TRIETHYLAMINE

Partition coefficient: soil/water 2,57

### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

### 12.7. Other adverse effects

Information not available

## SECTION 13. Disposal considerations

### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

**14.1. UN number or ID number**

not applicable

**14.2. UN proper shipping name**

not applicable

**14.3. Transport hazard class(es)**

not applicable

**14.4. Packing group**

not applicable

**14.5. Environmental hazards**

not applicable

**14.6. Special precautions for user**

not applicable

**14.7. Maritime transport in bulk according to IMO instruments**

Information not relevant

**SECTION 15. Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006Product

Point 3 - 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

VOC (Directive 2004/42/EC):

One - pack performance coatings.

**15.2. Chemical safety assessment**

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

**Flam. Liq. 2**

Flammable liquid, category 2

**159681 - - HYDRO MICACEO MT**

<b>Repr. 2</b>	Reproductive toxicity, category 2
<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>STOT RE 2</b>	Specific target organ toxicity - repeated exposure, category 2
<b>Skin Corr. 1A</b>	Skin corrosion, category 1A
<b>Eye Dam. 1</b>	Serious eye damage, category 1
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>Skin Sens. 1</b>	Skin sensitization, category 1
<b>Aquatic Acute 1</b>	Hazardous to the aquatic environment, acute toxicity, category 1
<b>Aquatic Chronic 1</b>	Hazardous to the aquatic environment, chronic toxicity, category 1
<b>Aquatic Chronic 3</b>	Hazardous to the aquatic environment, chronic toxicity, category 3
<b>H225</b>	Highly flammable liquid and vapour.
<b>H361d</b>	Suspected of damaging the unborn child.
<b>H361f</b>	Suspected of damaging fertility.
<b>H302</b>	Harmful if swallowed.
<b>H312</b>	Harmful in contact with skin.
<b>H332</b>	Harmful if inhaled.
<b>H373</b>	May cause damage to organs through prolonged or repeated exposure.
<b>H314</b>	Causes severe skin burns and eye damage.
<b>H318</b>	Causes serious eye damage.
<b>H319</b>	Causes serious eye irritation.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.
<b>H317</b>	May cause an allergic skin reaction.
<b>H400</b>	Very toxic to aquatic life.
<b>H410</b>	Very toxic to aquatic life with long lasting effects.
<b>H412</b>	Harmful to aquatic life with long lasting effects.

## LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train

**159681 - - HYDRO MICACEO MT**

- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

## GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
  4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
  11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
  12. Regulation (EU) 2016/1179 (IX Atp. CLP)
  13. Regulation (EU) 2017/776 (X Atp. CLP)
  14. Regulation (EU) 2018/669 (XI Atp. CLP)
  15. Regulation (EU) 2019/521 (XII Atp. CLP)
  16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
  17. Regulation (EU) 2019/1148
  18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
  19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
  20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
  21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
  22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - IFA GESTIS website
  - ECHA website
  - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

## Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

## CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

## Changes to previous review:

The following sections were modified:

02 / 03 / 08 / 09 / 10 / 11 / 12 / 15 / 16.