

## Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: 160255-  
Product name: HYDROGUARD Finish HG

1.2. Relevant identified uses of the substance or mixture and uses advised against  
Intended use: Component "A" for two components water based paint.

#### 1.3. Details of the supplier of the safety data sheet

Name: Ti.Pi.Ci. S.a.s.  
Full address: Via Val Lerone, 21  
District and Country: 16011 Arenzano (GE)  
Italy  
Tel. +39 010 9111368  
Fax +39 010 9134188

e-mail address of the competent person  
responsible for the Safety Data Sheet

laboris@tipici.net

#### 1.4. Emergency telephone number

For urgent inquiries refer to

Centro Antiveleni di Bergamo +39800883300 (Azienda Ospedaliera Papa Giovanni XXII - Bergamo)  
Centro Antiveleni di Firenze +39055/7947819 (CAV Ospedale Careggi - Firenze)  
Centro Antiveleni di Foggia +39800183459 (Az. Osp. Univ. Foggia - Foggia)  
Centro Antiveleni di Milano +3902/66101029 (CAO Ospedale Niguarda Cà Granda - Milano)  
Centro Antiveleni di Napoli +39081/5453333 (CAV Ospedale Cardarelli - Napoli)  
Centro Antiveleni di Pavia +390382/24444 (CAV IRCCS Fondazione Maugeri - Pavia)  
Centro Antiveleni di Roma +3906/3054343 (CAV Policlinico Gemelli - Roma)  
Centro Antiveleni di Roma +3906/49978000 (CAV Policlinico Umberto I - Roma)  
Centro Antiveleni di Roma +3906/68593726 (CAV Osp. Pediatrico Bambino Gesù - Roma)  
Centro Antiveleni di Verona +39800011858 (Azienda Ospedaliera Integrata - Verona)

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2020/878.  
Hazard classification and indication:

#### 2.2. Label elements

**160255- - HYDROGUARD Finish HG**

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal words: --

Hazard statements:

**EUH210** Safety data sheet available on request.

Precautionary statements:

--

VOC (Directive 2004/42/EC):

Two - pack performance coatings.

VOC given in g/litre of product in a ready-to-use condition :	60,24
Limit value:	140,00
- Catalysed with :	25,00 % CAT. per HYDROGUARD Finish HG

### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

## SECTION 3. Composition/information on ingredients

### 3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
<b>1-METHOXY-2-PROPANOL</b>		
INDEX 603-064-00-3	$4 \leq x < 4,5$	Flam. Liq. 3 H226, STOT SE 3 H336
EC 203-539-1		
CAS 107-98-2		
REACH Reg. 01-2119457435-35-XXXX		
<b>Paraffin (petroleum) normal C5-20</b>		
INDEX -	$1 \leq x < 1,5$	Asp. Tox. 1 H304
EC 265-233-4		
CAS 64771-72-8		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## SECTION 4. First aid measures

### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

## SECTION 5. Firefighting measures

### 5.1. Extinguishing media

#### SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

#### UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

### 5.2. Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

### 5.3. Advice for firefighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

**160255- - HYDROGUARD Finish HG**

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**6.4. Reference to other sections**

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage****7.1. Precautions for safe handling**

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

**7.2. Conditions for safe storage, including any incompatibilities**

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

**7.3. Specific end use(s)**

Information not available

**SECTION 8. Exposure controls/personal protection****8.1. Control parameters**

Regulatory References:

DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2021

**1-METHOXY-2-PROPANOL****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	370	100	740	200	
MAK	DEU	370	100	740	200	
VLA	ESP	375	100	568	150	SKIN
VLEP	FRA	188	50	375	100	SKIN
VLEP	ITA	375	100	568	150	SKIN
WEL	GBR	375	100	560	150	SKIN

**160255- - HYDROGUARD Finish HG**

OEL	EU	375	100	568	150	SKIN
TLV-ACGIH		184	50	368	100	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

## 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

### RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## SECTION 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	viscous liquid	
Colour	different colours	
Odour	characteristic	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	

**160255- - HYDROGUARD Finish HG**

Upper explosive limit	not available
Flash point	> 65 °C
Auto-ignition temperature	not available
Decomposition temperature	not available
pH	7
Kinematic viscosity	not available
Solubility	miscible with water
Partition coefficient: n-octanol/water	not available
Vapour pressure	not available
Density and/or relative density	1,21 (+-) 0,050
Relative vapour density	not available
Particle characteristics	not applicable

**9.2. Other information**

## 9.2.1. Information with regard to physical hazard classes

Information not available

## 9.2.2. Other safety characteristics

VOC (Directive 2004/42/EC) : 5,76 % - 69,75 g/litre

VOC (volatile carbon) 2,32 % - 28,03 g/litre

**SECTION 10. Stability and reactivity****10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

## 1-METHOXY-2-PROPANOL

Dissolves various plastic materials. Stable in normal conditions of use and storage.

Absorbs and dissolves in water and in organic solvents. With air it may slowly form explosive peroxides.

**10.2. Chemical stability**

The product is stable in normal conditions of use and storage.

**10.3. Possibility of hazardous reactions**

The vapours may also form explosive mixtures with the air.

## 1-METHOXY-2-PROPANOL

May react dangerously with: strong oxidising agents, strong acids.

**10.4. Conditions to avoid**

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

1-METHOXY-2-PROPANOL

Avoid exposure to: air.

#### 10.5. Incompatible materials

1-METHOXY-2-PROPANOL

Incompatible with: oxidising substances, strong acids, alkaline metals.

#### 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

## SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Metabolism, toxicokinetics, mechanism of action and other information

Information not available

##### Information on likely routes of exposure

1-METHOXY-2-PROPANOL

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

##### Delayed and immediate effects as well as chronic effects from short and long-term exposure

1-METHOXY-2-PROPANOL

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product. Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported.

**160255- - HYDROGUARD Finish HG**Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:	Not classified (no significant component)
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	Not classified (no significant component)

1-METHOXY-2-PROPANOL

LD50 (Dermal):	13000 mg/kg Rabbit
LD50 (Oral):	5300 mg/kg Rat
LC50 (Inhalation vapours):	54,6 mg/l/4h Rat

Paraffin (petroleum) normal C5-20

LD50 (Dermal):	> 2000 mg/kg coniglio
LD50 (Oral):	> 2000 mg/kg ratto
LC50 (Inhalation mists/powders):	> 5 mg/l/4h ratto

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class



REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

**11.2. Information on other hazards**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

**SECTION 12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

**12.1. Toxicity**

Paraffin (petroleum) normal C5-20

LC50 - for Fish

> 5000 mg/l/96h Pimephales promelas

**12.2. Persistence and degradability**

1-METHOXY-2-PROPANOL

Solubility in water

1000 - 10000 mg/l

Rapidly degradable

**12.3. Bioaccumulative potential**

1-METHOXY-2-PROPANOL

Partition coefficient: n-octanol/water

< 1

**12.4. Mobility in soil**

Information not available

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

#### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

#### 12.7. Other adverse effects

Information not available

### SECTION 13. Disposal considerations

#### 13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

### SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

#### 14.1. UN number or ID number

not applicable

#### 14.2. UN proper shipping name

not applicable

#### 14.3. Transport hazard class(es)

not applicable

#### 14.4. Packing group

not applicable

#### 14.5. Environmental hazards

not applicable

#### 14.6. Special precautions for user

not applicable

#### 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

### SECTION 15. Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

##### Product

Point 40

##### Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage  $\geq$  than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

**160255- - HYDROGUARD Finish HG**

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

VOC (Directive 2004/42/EC) :

Two - pack performance coatings.

### 15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

## SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Flam. Liq. 3</b>	Flammable liquid, category 3
<b>Asp. Tox. 1</b>	Aspiration hazard, category 1
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>H226</b>	Flammable liquid and vapour.
<b>H304</b>	May be fatal if swallowed and enters airways.
<b>H336</b>	May cause drowsiness or dizziness.
<b>EUH210</b>	Safety data sheet available on request.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level

**160255- - HYDROGUARD Finish HG**

- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

## GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
  4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
  10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
  11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
  12. Regulation (EU) 2016/1179 (IX Atp. CLP)
  13. Regulation (EU) 2017/776 (X Atp. CLP)
  14. Regulation (EU) 2018/669 (XI Atp. CLP)
  15. Regulation (EU) 2019/521 (XII Atp. CLP)
  16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
  17. Regulation (EU) 2019/1148
  18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
  19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
  20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
  21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
  22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - IFA GESTIS website
  - ECHA website
  - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

## Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

## CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

## Changes to previous review:

The following sections were modified:

02 / 03 / 08 / 09 / 10 / 11 / 12 / 13 / 15 / 16.