Ti.Pi	.Ci. S.a.s.	Revision nr. 5
		Dated 21/11/2022
160377-100745 - CAT.	per HYDROGUARD Novolac	Printed on 21/11/2022
		Page n. 1/13
		Replaced revision:4 (Dated: 12/03/2021)
Safety Data Sheet According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH		
SECTION 1. Identification of the Sub	stance/mixture and of the company/unde	laking
1.1. Product identifier Code: Product name	160377-100745 CAT. per HYDROGUARD Novolac	
1.2. Relevant identified uses of the substance or in Intended use Hardener for two control	mixture and uses advised against mponents water based paint.	
1.3. Details of the supplier of the safety data shee	t	
Name Full address District and Country	Ti.Pi.Ci. S.a.s. Via Val Lerone, 21 16011 Arenzano (GE) Italy	
	Tel. +39 010 9111368	
	Fax +39 010 9134188	
e-mail address of the competent person		
responsible for the Safety Data Sheet	laboris@tipici.net	
1.4. Emergency telephone number For urgent inquiries refer to	Centro Antiveleni di Bergamo +39800883300 (Azienda G Bergamo) Centro Antiveleni di Firenze +39055/7947819 (CAV Osp Centro Antiveleni di Foggia +39800183459 (Az. Osp. Ur Centro Antiveleni di Milano +3902/66101029 (CAO Ospe Milano) Centro Antiveleni di Napoli +39081/5453333 (CAV Ospe Centro Antiveleni di Pavia +39082/24444 (CAV IRCCS Centro Antiveleni di Roma +3906/3054343 (CAV Policili Centro Antiveleni di Roma +3906/49978000 (CAV Policili Centro Antiveleni di Roma +3906/68593726 (CAV Osp. 1 Roma) Centro Antiveleni di Verona +39800011858 (Azienda Os	edale Careggi - Firenze) niv. Foggia - Foggia) edale Niguarda Cà Granda - edale Cardarelli - Napoli) Fondazione Maugeri - Pavia) nico Gemelli - Roma) inico Umberto I - Roma) Pediatrico Bambino Gesù -

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:	
Eye irritation, category 2	H319
Skin irritation, category 2	H315
Specific target organ toxicity - single exposure, category 3	H335
Hazardous to the aquatic environment, acute toxicity,	H400

Causes serious eye irritation. Causes skin irritation. May cause respiratory irritation. Very toxic to aquatic life.

	Ti.Pi.Ci. S.a.s.	Revision nr. 5
		Dated 21/11/2022
16037	7-100745 - CAT. per HYDROGUARD Novolac	Printed on 21/11/2022
		Page n. 2/13
		Replaced revision:4 (Dated: 12/03/2021)
category 1 Hazardous to the aquatic category 1	environment, chronic toxicity, H410 Very toxic to aquatic life with	h long lasting effects.
2.2. Label elements		
Hazard labelling pursuant to	DEC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.	
Hazard pictograms:		
Signal words:	Warning	
Hazard statements:		
H319	Causes serious eye irritation.	
H315 H335	Causes skin irritation. May cause respiratory irritation.	
H410	Very toxic to aquatic life with long lasting effects.	
Precautionary statements:		
P273 P391 P261 P280 P312 P403+P233	Avoid release to the environment. Collect spillage. Avoid breathing dust / fume / gas / mist / vapours / spray. Wear protective gloves / eye protection / face protection. Call a POISON CENTRE / doctor / if you feel unwell. Store in a well-ventilated place. Keep container tightly closed.	
Contains:	Neodecanoic acid, 2-oxiranylmethyl ester, reaction products with bisphenol A-bisphenol glycidyl o-tolyl ether, 2-methyl-1,5-pentanediamine, oxidized polyethylene glycol and trie	
2.3. Other hazards		
On the basis of available da	ata, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.	
The product does not conta	in substances with endocrine disrupting properties in concentration $\ge 0.1\%$.	
SECTION 3. Com	position/information on ingredients	
3.2. Mixtures		
Contains:		
Identification Neodecanoic acid, 2-	x = Conc. % Classification (EC) 1272/2008 (CLP)	
oxiranylmethyl ester, rea	ction	

Ti.Pi.Ci. S.a.s.

160377-100745 - CAT. per HYDROGUARD Novolac

Revision nr. 5 Dated 21/11/2022 Printed on 21/11/2022 Page n. 3/13 Replaced revision:4 (Dated: 12/03/2021)

products with bisphenol Abisphenol A diglycidyl ether polymer, glycidyl o-tolyl ether, 2methyl-1,5-pentanediamine, oxidized polyethylene glycol and triethylenetetramine INDEX

50	≤ x	<	90
----	-----	---	----

Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1

EC -CAS 219687-87-3

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Wash immediately with plenty of water. If irritation persists, get medical advice/attention. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. In the event of breathing difficulties, get medical advice/attention immediately.

INGESTION: Get medical advice/attention. Induce vomiting only if indicated by the doctor. Never give anything by mouth to an unconscious person, unless authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

160377-100745 - CAT. per HYDROGUARD Novolac

Ti.Pi.Ci. S.a.s.

Revision nr. 5

Dated 21/11/2022 Printed on 21/11/2022

Page n. 4/13

Replaced revision:4 (Dated: 12/03/2021)

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Information not available

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Integration Measure on 2111 (2022) Pages at 13 Page of 211 Provide an emergency shower with face and eye wash station. Med DPOIECTION Mean and with category III work gloves (see standard EN 372). The following structure does not be indexed on the output organization of all the constructure with the consthere with the constructure with the consthere with the construct		Ti.Pi.Ci. S.a.s.		Revision nr. 5 Dated 21/11/2022
Pipe 33 Pipe 43 Pipe 44 Pipe	160277 100715			
an emergency shower with face and eye wash station. NDP PROTECTION are adapting should be considered when choosing work give material: compatibility, degradation, failure time and permeability. e following should be considered when choosing work give material: compatibility, degradation, failure time and permeability. e vork gives" restance to chemical agents should be checked before use, as It can be unpredictable. The gloves' wear time depends on the durat d type of use. IN PROTECTION are category II professional long-sleaved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with se d water after removing protective cothing. E PROTECTION are category II professional long-sleaved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with se d water after removing protective cothing. SSPIEATORY PROTECTION he threshold white (sg. TV-TWA) is exceeded for the substance or one of the substances present in the product, use a mark with a type B fit onse class (1, 2 or 3) must be chosen according to the limit of use concentration, (see standard EN 1337) or a correct the protection provide b marks is in any case limited. He usobalance considered in educates or its offactory threshold is higher than the corresponding TV-TWA and in the cases of a neergine, w encicular compressed at b beating appartus (in compliance with standard EN 137) or a correct tholes of respiratory protection devices, see standard EN 1320 or actinate breathing appartus (in compliance with encicular compleased at b beathing appartus (in compliance with standard EN 1320 or actinate breathing appartus (in compliance with encicular compleased ato beathing appartus (in compliance with standard EN 1320 or acorec	160377-100745	CAL per HIDROG	UARD NOVOIAC	Page n. 5/13
NUPROTECTION To the standard EN 374), the following volume have have a standard EN 374), the following should be considered when choosing work gives matrixel: compatibility, degradation, failure time and permeability. The work gives' resistance to chemical agents should be checked before use, as it can be unpredictable. The gives' wear time depends on the durat dives of use. IN PROTECTION Ear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with sc divater after removing protective clothing. YE PROTECTION Ear artight professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with sc divater after removing protective clothing. YE PROTECTION Ear artight professional long-sleeved overalls and safety footwear or one of the substances present in the product, use a mask with a type B fi mase class (1, 2 or 3) must be chosen according to the limit of use concentration (see standard EN 1437). In the presence of gases or vapours nois kinds and/or gases or vapours containing particulate (acrosol sprays, times, mists et b) combined fifters are required. spratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threah the subdance considered is odoutly threshold is higher than the corseponding TLV-TWA and in the case of an emergency, wench with standard EN 137) or external air-intake breathing apparatus (in compliance v andard EN 137) or external air-intake breathing apparatus (in compliance v winomental standards. Section 9. Physical and chemical properties Properties Value Value Information Appearance Viscous liquid Colour Vinte Value Information Appearance Viscous liquid Colour Vinte Appearance Value Information Appearance Viscous liquid Colour Vinte Appearance Value Information Appearance Value Information Appearance Value Information Appearance Value Information Appearance Value Appearance Value				Replaced revision:4 (Dated: 12/03/2021)
totect hands with category III work gloves (see standard EN 374). te work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the durat d type of use. IN PROTECTION aer category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 2034). Wash body with sci d water after removing protective clothem. <i>RE</i> PROTECTION mer artifyith protective goggles (see standard EN 166). <i>ESPIRATORY</i> PROTECTION the threshold value (e.g., TLV-1WA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B finate class (1, 2, cl 3) must be chosen according to the limit of use concentration (see standard EN 14367). In the presence of gases or vapour nois kinds and/or gases or vapours containing particulate (aeroos Darys, fume, miss): etc.) combined first are required. The substance considered is double (e.g. TLV-1WA) is exceeded for the substance with standard EN 14367). In the presence of gases or vapours nois kinds and/or gases or vapours containing particulate (aeroos Darys, fume, miss): etc.) combined first are required. The substance considered is double (e.g. TLV-1WA) is exceeded for the substance with standard EN 137) or external ai-intake breathing apparatus (in compliance with standard EN 137) or external ai-intake breathing apparatus (in compliance with standard EN 137). For accord choise or support of the value of the value of the substance or support of respiratory protection drew with sci support of respiratory properties ERECTION 9. Physical and churc: I properties Properties Value Value V	ovide an emergency shower with face and	d eye wash station.		
ear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with so diver after removing protective clothing. ESPIRATORY PROTECTION ear airtight protective goggles (see standard EN 166). ESPIRATORY PROTECTION the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B fi nose class (1, 2 or 3) must be closen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapour nous kinds and/or gases or vapours containing particulate (aeroso) sprays, fumes, mists, etc.) combined filters are required. Espiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the thresh lies considered. The protection provided by masks is in any case limited. Interpretent of the substance or entor table in the case of an emergency, w andard EN 138). For a correct choice of respiratory protection device, see standard EN 137) or external air-intake breathing apparatus (in compliance w andard EN 138). For a correct choice of respiratory protection device, see standard EN 529. WIRONMENTAL EXPOSURE CONTROLS te emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance w information on basic physical and checked of with waste water or by dumping in waterways. SECTION 9. Physical and checked to available Limital boiling point not available Liper explosive limit not availab	otect hands with category III work gloves on the following should be considered when ch he work gloves' resistance to chemical age	hoosing work glove material: cor		
ear airtight protective goggles (see standard EN 166).	ear category II professional long-sleeved		ee Regulation 2016/425 and stan	dard EN ISO 20344). Wash body with soa
the threshold value (e.g., TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B I, so certain (1, 2 or 3) must be obseen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours rous kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mist, etc.) combined filters are required. spiratory protection perovided by masks is in any case limited. the substance considered is obsurdess or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, w en-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with andard EN 138). For a correct choice of respiratory protection device, see standard EN 529. VIRONMENTAL EXPOSURE CONTROLS e emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with standards. oduct residues must not be indiscriminately disposed of with waste water or by dumping in waterways. SECTION 9. Physical and cherres in properties Properties Value Appearance Colour white Colour white Colour slightly amine Welting point / freezing point not available rammability not available rammability not available rammability not available cover explosive limit not available rampability not available cover explosive limit not available rampability not available cover explosive limit net reas available cover explosive limit net reas available cover explosive limit net reas available cover explosive limit net available cover explosiv		ard EN 166).		
e emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance v vironmental standards. oduct residues must not be indiscriminately disposed of with waste water or by dumping in waterways. SECTION 9. Physical and chemical properties 9.1. Information on basic physical and chemical properties Properties Value Information Appearance Colour Colour Viscous liquid Colour Melting point / freezing point Not a vailable Flammability Lower explosive limit Lower explosive limit Decomposition temperature Not available Flash point Patheting point Not available Plash point Decomposition temperature Not available Plash point Not available Plash point Decomposition temperature Not available Decomposition temperature Not available Decomp	the threshold value (e.g. TLV-TWA) is ex- nose class (1, 2 or 3) must be chosen ac irious kinds and/or gases or vapours conta espiratory protection devices must be use ilues considered. The protection provided the substance considered is odourless of pen-circuit compressed air breathing appa andard EN 138). For a correct choice of re	ecording to the limit of use conc aining particulate (aerosol sprays ed if the technical measures ac by masks is in any case limited. r its olfactory threshold is highe aratus (in compliance with stan espiratory protection device, see	entration. (see standard EN 1438 s, fumes, mists, etc.) combined filt lopted are not suitable for restric r than the corresponding TLV-TV dard EN 137) or external air-intal	37). In the presence of gases or vapours of ers are required. ting the worker's exposure to the threshol VA and in the case of an emergency, weat
An Information on basic physical and chemical properties Properties Value Information Appearance viscous liquid Colour white Odour slightly amine Aelting point / freezing point not available Information not available Iditing point / freezing point not available Iditing point not available Iditin temperature not available <tr< th=""><th>vironmental standards.</th><th></th><th></th><th>nould be checked to ensure compliance wi</th></tr<>	vironmental standards.			nould be checked to ensure compliance wi
Properties Value Information Appearance viscous liquid Colour white Odour slightly amine Odour slightly amine Melting point / freezing point not available Initial boiling point not available Flammability not available Lower explosive limit not available Upper explosive limit not available Ish point not available Properties not available Decomposition temperature not available pd not available pd <t< th=""><th>SECTION 9. Physical and cho</th><th>emical properties</th><th></th><th></th></t<>	SECTION 9. Physical and cho	emical properties		
Appearanceviscous liquidColourwhiteOdourslighty amineMelting point / freezing pointnot availableInitial boiling pointnot availableInitial boiling pointnot availableLower explosive limitnot availableUpper explosive limitnot availablePlash pointnot availableInto availablenot availableInto availablenot availablePlash pointnot availablePlash point> 65 °CAuto-ignition temperaturenot availableDecomposition temperaturenot availableDef10Kinematic viscositynot availableDynamic viscosity8.000 mPa·s @25 °CSolubilitymiscible with water	9.1. Information on basic physical and o	chemical properties		
ColourwhiteColourslightly amineMelting point / freezing pointnot availablenitial boiling pointnot availableTammabilitynot availableLower explosive limitnot availableLower explosive limitnot availableJpper explosive limitnot availableFlash point> 65 °CAuto-ignition temperaturenot availableDecomposition temperaturenot ava	Properties	Value	Information	
Doorslightly amineMelting point / freezing pointnot availablenitial boiling pointnot availableFlammabilitynot availableower explosive limitnot availableower explosive limitnot availableJpper explosive limitnot availableJoper explosive limitnot availableVacio-ignition temperaturenot availableOccomposition temperaturenot availableOH10Kinematic viscositynot availableOpnamic viscosity8.000 mPa ·s @25 °CSolubilitymiscible with water				
Melting point / freezing point not available nitial boiling point not available Flammability not available cower explosive limit not available cower explosive limit not available Jpper explosive limit not available Flash point > 65 °C Auto-ignition temperature not available Decomposition temperature not available OH 10 Kinematic viscosity not available Oynamic viscosity 8.000 mPa·s @25 °C Solubility miscible with water	oppearance	viscous liquid		
Initial boiling pointnot availableInitial boiling pointnot availableInternabilitynot availableInternabilitynot availableInternabilitynot availableInternational point> 65 °CAuto-ignition temperaturenot availableDecomposition temperaturenot availableInternational point10Kinematic viscositynot availableDynamic viscosity8.000 mPa·s @25 °CSolubilitymiscible with water				
Flammabilitynot availablecower explosive limitnot availableUpper explosive limitnot availableFlash point> 65 °CAuto-ignition temperaturenot availableDecomposition temperaturenot available0H10Kinematic viscositynot availableDynamic viscosity8.000 mPa·s @25 °CSolubilitymiscible with water	Colour	white		
AverageNot availableJoper explosive limitnot availableFlash point> 65 °CAuto-ignition temperaturenot availableDecomposition temperaturenot availableH10Kinematic viscositynot availableDynamic viscosity8.000 mPa·s @25 °CSolubilitymiscible with water	Colour Odour	white slightly amine		
AverageNot availableJoper explosive limitnot availableFlash point> 65 °CAuto-ignition temperaturenot availableDecomposition temperaturenot availableH10Kinematic viscositynot availableDynamic viscosity8.000 mPa·s @25 °CSolubilitymiscible with water	Colour Ddour Melting point / freezing point	white slightly amine not available		
Upper explosive limitnot availableFlash point> 65 °CAuto-ignition temperaturenot availableDecomposition temperaturenot a	Colour Colour Melting point / freezing point nitial boiling point	white slightly amine not available not available		
Flash point > 65 °C Auto-ignition temperature not available Decomposition temperature not available DH 10 Kinematic viscosity not available Dynamic viscosity 8.000 mPa·s @25 °C Solubility miscible with water	Colour Colour Melting point / freezing point nitial boiling point Flammability	white slightly amine not available not available not available		
Auto-ignition temperaturenot availableDecomposition temperaturenot availableDH10Kinematic viscositynot availableDynamic viscosity8.000 mPa·s @25 °CSolubilitymiscible with water	Colour Colour Melting point / freezing point nitial boiling point Flammability Lower explosive limit	white slightly amine not available not available not available not available		
Decomposition temperature not available bH 10 Kinematic viscosity not available Dynamic viscosity 8.000 mPa·s @25 °C Solubility miscible with water	Colour Colour Ddour Melting point / freezing point nitial boiling point Flammability Lower explosive limit Jpper explosive limit	white slightly amine not available not available not available not available not available		
bH 10 Kinematic viscosity not available Dynamic viscosity 8.000 mPa·s @25 °C Solubility miscible with water	Colour Colour Ddour Melting point / freezing point nitial boiling point Flammability Lower explosive limit Jpper explosive limit Flash point	white slightly amine not available not available not available not available > 65 °C		
Kinematic viscositynot availableDynamic viscosity8.000 mPa·s @25 °CSolubilitymiscible with water	Colour Colour Ddour Melting point / freezing point nitial boiling point Flammability Lower explosive limit Jpper explosive limit Flash point Auto-ignition temperature	white slightly amine not available not available not available not available > 65 °C not available		
Dynamic viscosity 8.000 mPa·s @25 °C Solubility miscible with water	Colour Colour Odour Melting point / freezing point nitial boiling point Flammability Lower explosive limit Jpper explosive limit Flash point Auto-ignition temperature Decomposition temperature	white slightly amine not available not available not available not available > 65 °C not available not available		
Solubility miscible with water	Colour Colour Odour Melting point / freezing point Initial boiling point Flammability Lower explosive limit Upper explosive limit Flash point Auto-ignition temperature Decomposition temperature oH	white slightly amine not available not available not available not available > 65 °C not available not available 10		
•	Colour Colour Odour Melting point / freezing point Initial boiling point Flammability Lower explosive limit Upper explosive limit Flash point Auto-ignition temperature Decomposition temperature pH Kinematic viscosity	white slightly amine not available not available not available not available > 65 °C not available not available 10 not available		
	Colour Odour Melting point / freezing point Initial boiling point Flammability Lower explosive limit Upper explosive limit Flash point Auto-ignition temperature Decomposition temperature pH Kinematic viscosity Dynamic viscosity	white slightly amine not available not available not available not available $> 65 \degree C$ not available not available 10 not available 8.000 mPa s @25 °C		

Revision nr. 5 Ti.Pi.Ci. S.a.s. Dated 21/11/2022 160377-100745 - CAT. per HYDROGUARD Novolac 3/2021)

Baloa E III III EOEE
Printed on 21/11/2022
Page n. 6/13
Replaced revision:4 (Dated: 12/03/

not available
1,088 kg/l
not available
not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Ti.Pi.Ci. S	as	Revision nr. 5
		Dated 21/11/2022
160377-100745 - CAT. per H	YDROGUARD Novolac	Printed on 21/11/2022
		Page n. 7/13
		Replaced revision:4 (Dated: 12/03/2021)
Metabolism, toxicokinetics, mechanism of action and other info	rmation	
Information not available		
Information on likely routes of exposure		
Information not available		
Delayed and immediate effects as well as chronic effects from	short and long-term exposure	
Information not available		
Interactive effects		
Information not available		
ACUTE TOXICITY		
ATE (Inhalation) of the mixture:	Not classified (no significant component)	
ATE (Oral) of the mixture:	Not classified (no significant component)	
ATE (Dermal) of the mixture:	Not classified (no significant component)	
SKIN CORROSION / IRRITATION		
Causes skin irritation		
SERIOUS EYE DAMAGE / IRRITATION		
Causes serious eye irritation		
RESPIRATORY OR SKIN SENSITISATION		
Does not meet the classification criteria for this hazard class		
GERM CELL MUTAGENICITY		

160377-100745 - CAT. per HYDROGUARD Novolac	Revision nr. 5 Dated 21/11/2022 Printed on 21/11/2022 Page n. 8/13 Replaced revision:4 (Dated: 12/03/2021)

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause respiratory irritation

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and highly toxic for aquatic organisms. In the long term, it have negative effects on aquatic environment. **12.1. Toxicity**

Information not available

12.2. Persistence and degradability

Information not available

Ti.Pi.Ci. S.a.s.	Revision nr. 5
	Dated 21/11/2022
160377-100745 - CAT. per HYDROGUARD Novolac	Printed on 21/11/2022
	Page n. 9/13

Replaced revision:4 (Dated: 12/03/2021)

12.3. Bioaccumulative potential

Information not available

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

_....

14.1. UN number or ID number

. _ _ . _ . _

ADR / RID, IMDO	G, IATA: 3082
ADR / RID:	In accordance with Special Provision 375, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not submitted to ADR provisions.
IMDG:	In accordance with Section 2.10.2.7 of IMDG Code, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not submitted to IMDG Code provisions.
IATA:	In accordance with SP A197, this product, when is packed in receptacles of a capacity ≤ 5Kg or 5L, is not submitted to IATA dangerous goods regulations.
14.2. UN proper s	hipping name

ADR / RID:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Neodecanoic acid, 2-oxiranylmethyl ester,
	reaction products with bisphenol A-bisphenol A diglycidyl ether polymer, glycidyl o-tolyl ether, 2-methyl-1,5-
	pentanediamine, oxidized polyethylene glycol and triethylenetetramine)
IMDG:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Neodecanoic acid, 2-oxiranylmethyl ester,
	reaction products with bisphenol A-bisphenol A diglycidyl ether polymer, glycidyl o-tolyl ether, 2-methyl-1,5-

.....

		5 - CAT. per HYDROG	UARD Novola	C	Dated 21/11/2022 Printed on 21/11/2022
	nentanediamin				Page n. 10/13
1474.	pentanediamin				Replaced revision:4 (Dated: 12/03/2021)
IATA:	ENVIRONMEN reaction produc	e, oxidized polyethylene glycol and TALLY HAZARDOUS SUBSTANC ts with bisphenol A-bisphenol A dig e, oxidized polyethylene glycol and	E, LIQUID, N.O.S. (Ne glycidyl ether polymer,	eodecanoic acid, 2-o glycidyl o-tolyl ether	oxiranylmethyl ester, r, 2-methyl-1,5-
I4.3. Transport haza	ard class(es)				
ADR / RID:	Class: 9	Label: 9	A.		
IMDG:	Class: 9	Label: 9	, M		
IATA:	Class: 9	Label: 9			
I4.4. Packing group)				
ADR / RID, IMDG, I	IATA:	III			
14.5. Environmental	l hazards				
ADR / RID:	Environmentall Hazardous	у			
IMDG:	Marine Pollutar	nt			
IATA:	Environmentall Hazardous	у			
I4.6. Special precau	itions for user				
ADR / RID:		HIN - Kemler: 90		Limited Quantities: 5 L	Tunnel restriction code: (-)
		Special provision: -		L	codc. (-)
IMDG:		EMS: F-A, S-F		Limited Quantities: 5 L	
IATA:		Cargo:		Maximum quantity: 450 L	Packaging instructions: 964
		Pass.:		L Maximum quantity: 450 L	Packaging instructions: 964
		Special provision:		A97, A158, A197, A215	
4.7. Maritime trans	port in bulk accor	ding to IMO instruments			
nformation not releva	ant				

SECTION 15. Regulatory information

Ti.Pi.Ci. S.a.s.	Revision nr. 5 Dated 21/11/2022	
160377-100745 - CAT. per HYDROGUARD Novolac	Printed on 21/11/2022	
	Page n. 11/13	
	Replaced revision:4 (Dated: 12/03/2021)	
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture		
eveso Category - Directive 2012/18/EU: E1		
estrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006		
roduct Point 3		
egulation (EU) 2019/1148 - on the marketing and use of explosives precursors		
ot applicable		
ubstances in Candidate List (Art. 59 REACH)		
In the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.		
ubstances subject to authorisation (Annex XIV REACH)		
one		
ubstances subject to exportation reporting pursuant to Regulation (EU) 649/2012:		
one		
ubstances subject to the Rotterdam Convention:		
one		
ubstances subject to the Stockholm Convention:		
one		
ealthcare controls		
orkers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment o orkers' health and safety are modest and that the 98/24/EC directive is respected.	data prove that the risks related to th	
15.2. Chemical safety assessment		
chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.		
SECTION 16. Other information		

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1

160377-100745 - CAT. per HYDROGUARD Novolac

Ti.Pi.Ci. S.a.s.

Revision nr. 5 Dated 21/11/2022 Printed on 21/11/2022 Page n. 12/13 Replaced revision:4 (Dated: 12/03/2021)

- H319 Causes serious eye irritation.
- H315 Causes skin irritation.
- May cause respiratory irritation. H335
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- **OEL: Occupational Exposure Level**
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- Regulation (EU) 2020/878 (II Annex of REACH Regulation)
 Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP) 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP) 21. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition

160377-100745 - CAT. per HYDROGUARD Novolac

Ti.Pi.Ci. S.a.s.

Revision nr. 5 Dated 21/11/2022

Printed on 21/11/2022

Page n. 13/13 Replaced revision:4 (Dated: 12/03/2021)

Handling Chemical Safety

- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website

ECHA website

- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property. The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety

laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified: 02 / 09 / 11 / 12 / 14 / 15 / 16.